Alloy 263

Smiths Advanced Metals

Rev: SAM/datasheets/nickel-alloys/alloy-263-bars/aug-2023



Page: 1 of 1

Nickel Cobalt Based Alloy Bars

Alloy 263 is a nickel-cobalt-chromium-molybdenum alloy which offers good aged-hardened characteristics.

The material combines various performance characteristics resulting in a highly capable engineering material - the product benefits from high-temperature strength, high corrosion resistance, good weldability and forming capabilities.


Alloy 263 displays excellent oxidation resistance. While Alloy 263 does not offer the best high-temperature performance, it is much easier to form and weld. Material forming is straightforward by cold working.

Commercial Applications

The alloy was originally developed for aerospace engines but has expanded its appeal to other market areas, such as advanced ultra-supercritical power plants (A-USC). The alloy finds regular use in producing aircraft engine cases, gas turbine rings and low-temperature combusters. Material strength is retained up to 816°C and oxidation resistance up to 982°C.

Benefits

- High-temperature strength
- Excellent oxidation resistance
- Easily formed and welded



Key Applications

- Gas turbine rings
- Aircraft engine casings
- Low-temperature combusters

Chemical Composition (weight %)																
	Ni	Cr	Mn	Si	С	Al	В	Fe	Cu	Мо	Со	Ti	Al+Ti	S	Р	
min.	Bal	19.00			0.04	0.30				5.60	19.00	1.90	2.40			
max.	Bal	21.00	0.60	0.40	0.08	0.60	0.005	0.70	0.20	6.10	21.00	2.40	2.80	0.007	0.015	

^{*} As per AMS 5886

Physical Properties	
Density	8.359 g/cm ³
Melting Range	1300-1355°C
Specific Heat Capacity	461 J/kg. °C
Electrical Resistivity	1.15 μΩ.m

Stock Availability

We stock bars of Alloy 263, which are available in various sizes, and we process your bar products in-house to precise lengths.

www. smiths advanced. com



Stratton Business Park, London Road, Biggleswade, Bedfordshire SG18 8QB

Tel: +44 (0) 1767 604710





info@smithsadvanced.com

1930